

The 'UNIVERS' universal plug expands in 3 directions in solid building materials (concrete, solid sand lime brick, brick or natural stone) and knots around the screw in hollow building materials (plasterboard, lightweight boards or perforated bricks). It is made of high-quality plastic and is suitable for use with wood and chipboard screws.

**Temperature resistance:** -40°F to +158°F

**Safety coefficient:** 5



### Product specification

Article Item number	Dimensions Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Box contents	outer carton
10 300	5 x 29	5	35	100 pcs.	8.000 pcs.
10 300	6 x 33	6	40	100 pcs.	8.000 pcs.
10 300	8 x 46	8	60	100 pcs.	2.000 pcs.
10 300	10 x 56	10	70	50 pcs.	1.000 pcs.
10 300	12 x 67	12	80	25 pcs.	1.000 pcs.
10 300	14 x 71	14	85	20 pcs.	800 pcs.

### Extraction values in kilo-Newton\*

Plug/Screw Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20	Plasterboard	Perforated brick
5 / 3,5	0,8 kN	0,7 kN	0,7 kN	0,6 kN	0,5 kN
6 / 4,0	1,1 kN	1,0 kN	1,0 kN	0,7 kN	0,7 kN
8 / 5,0	1,6 kN	1,4 kN	1,4 kN	1,0 kN	1,2 kN
10 / 6,0	1,9 kN	1,6 kN	1,6 kN	1,0 kN	1,4 kN
12 / 10,0	2,6 kN	2,3 kN	2,1 kN	1,1 kN	2,0 kN
14 / 12,0	3,9 kN	3,4 kN	3,3 kN	1,2 kN	3,2 kN

\* All data is based on values determined during factory tests by Hüfner-Dübel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

#### CONTACT US

☎ +49 (0) 3622 92040  
✉ office@huefner-duebel.de

#### OUR ADDRESS

Gothaer Straße 50  
D-99880 Waltershausen

#### ONLINE PRESENCE

🌐 www.huefner-duebel.de  
#Hüfner-Dübel GmbH