

Technical data sheet

nail plug "FIX A2" cylindrical head with stainless steel A2 screw nail

The nail plug "FIX A2" with cylindrical head made of pure nylon with pre-assembled stainless steel A2 screw nail is suitable for quick installations with high pull-out values in solid building materials. It can be subsequently adjusted using its cross recess. The cylindrical dowel head lies like a washer. This is important when fastening thin-walled add-on parts such as signs, sheet metal, metal studs and electrical cable ducts. The use of rust-resistant materials makes this fixing particularly suitable for outdoor use.



Temperature resistance: -40°F to +176°F

Safety coefficient: 5

Product specification

Article number	Plug-Dim. Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Installation deph min. mm	Effective length max. mm	Box contents	outer carton
11 052	5 x 30	5	30	20	10	200 pcs.	2.000 pcs.
11 052	5 x 40	5	30	20	20	200 pcs.	2.000 pcs.
11 052	5 x 50	5	30	20	30	200 pcs.	2.000 pcs.
11 052	5 x 60	5	30	20	40	200 pcs.	2.000 pcs.
11 052	6 x 30	6	35	25	5	200 pcs.	2.000 pcs.
11 052	6 x 35	6	35	25	10	200 pcs.	2.000 pcs.
11 052	6 x 40	6	35	25	15	200 pcs.	2.000 pcs.
11 052	6 x 50	6	35	25	25	200 pcs.	2.000 pcs.
11 052	6 x 60	6	35	25	35	200 pcs.	2.000 pcs.
11 052	6 x 80	6	35	25	55	200 pcs.	2.000 pcs.
11 052	8 x 60	8	45	40	20	100 pcs.	1.000 pcs.
11 052	8 x 80	8	45	40	40	100 pcs.	1.000 pcs.
11 052	8 x 100	8	45	40	60	100 pcs.	1.000 pcs.
11 052	8 x 120	8	45	40	80	100 pcs.	1.000 pcs.

ONLINE PRESENCE



Technical data sheet

nail plug "FIX A2" cylindrical head with stainless steel A2 screw nail

Extraction values in kilo-Newton*

Plug ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

^{*} All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.