

## Technical data sheet

nail plug "FIX-S" countersunk head with galvanised screw nail and galvanised washer

The nail plug "FIX-S" made of pure nylon with countersunk head, galvanised screw nail and galvanised washer ø 20 mm is suitable for quick fastening in solid building materials. It can be subsequently adjusted thanks to its cross slot and is recommended for fixing expanded metal, mesh metal and mesh fabric, for example.

**Temperature resistance:** -40°F to +176°F

Safety coefficient: 5



## Product specification

Article number	Dimensions Ø x L mm	Disc Ø mm	Drill Ø mm	Drilling depth min. mm	Setting depth min. mm	Effective length max. mm	Box contents	outer carton
11 070	6 x 35	20	6	35	25	10	100 pcs.	1.000 pcs.
11 070	6 x 40	20	6	35	25	15	100 pcs.	1.000 pcs.
11 070	6 x 50	20	6	35	25	25	100 pcs.	1.000 pcs.
11 070	6 x 60	20	6	35	25	35	100 pcs.	1.000 pcs.
11 070	6 x 80	20	6	35	25	55	100 pcs.	1.000 pcs.
11 070	8 x 50	20	8	45	40	10	100 pcs.	1.000 pcs.

## Extraction values in kilo-Newton\*

Plug ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

\* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

**ONLINE PRESENCE**