



Technical data sheet

nail plug „FIX-M“ countersunk head

The nail plug with metric connection thread "FIX-M" (anchor with countersunk head) made of pure nylon with galvanised threaded head screw nail is suitable for quick installations with high pull-out values in solid building materials. The area of application is, for example, the fastening of cable and pipe clamps with metric threads M6 & M8. The special head shape of the nail allows it to be driven into the anchor without damaging the metric thread.

Temperature resistance: -40°F to +176°F

Safety coefficient: 5



Product specification

Article number	Dowels-Dim. Ø x L mm	Attachment thread	Drill bit Ø mm	Drilling depth min. mm	Installation depth min. mm	Effective length max. mm	Box contents	outer carton
11 075	6 x 40	M 6	6	35	25	15	200 St.	2.000 St.
11 075	8 x 60	M 8	8	45	40	20	100 St.	1.000 St.

Extraction values in kilo-Newton*

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

* All data is based on values determined during factory tests by Hüfner-Dübel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH