



Technical data sheet

nail plug „FIX-COLOR“ countersunk head
brown

The "FIX-COLOR" nail plug made of pure nylon with countersunk head has a colour-coated screw nail. It is ideal for quick installation of wood, signs, skirting boards, wall connection profiles and many other objects where a visible, colour-coordinated fixing is required. It can be subsequently adjusted thanks to its cross recess.

Temperature resistance: -40°F to +176°F

Safety coefficient: 5



Product specification

Article number	Dimension Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Installation deph min. mm	Effective length max. mm	Box contents	outer carton
11 160	5 x 30	5	30	20	10	200 pcs.	2.000 pcs.
11 160	5 x 40	5	30	20	20	200 pcs.	2.000 pcs.
11 160	5 x 50	5	30	20	30	200 pcs.	2.000 pcs.
11 160	5 x 60	5	30	20	40	200 pcs.	2.000 pcs.

Extraction values in kilo-Newton^{*}

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
5	1,2 kN	1,1 kN	1,0 kN
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH