



# Technical data sheet

Frame plug nylon with screw "RKPF"  
Pozidrive mounting, hot-dip galvanised

The "RKPF" frame plug made of pure nylon with hot-dip galvanised Pozidrive screw enables fast and secure fastening in solid materials such as solid and natural stone, concrete and sand-lime brick. The hot-dip galvanisation provides a very high level of corrosion protection. Its 4 side wings reliably prevent the plug from turning while the screw is being screwed in.

**Temperature resistance:** -40°F to +176°F

**Safety coefficient:** 5



## Product specification

Article number	Dimension Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Installation depth min. mm	Effective length max. mm	Box contents	outer carton
11 205	10 x 80	10	60	50	30	50 pcs.	500 pcs.
11 205	10 x 100	10	60	50	50	50 pcs.	500 pcs.
11 205	10 x 120	10	60	50	70	50 pcs.	500 pcs.
11 205	10 x 140	10	60	50	90	50 pcs.	500 pcs.
11 205	10 x 160	10	60	50	110	50 pcs.	500 pcs.

## Extraction values in kilo-Newton\*

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
10	4,5 kN	3,9 kN	3,9 kN

\* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

### CONTACT US

☎ +49 (0) 3622 92040  
✉ office@huefner-duebel.de

### OUR ADDRESS

Gothaer Straße 50  
D-99880 Waltershausen

### ONLINE PRESENCE

🌐 www.huefner-duebel.de  
f #Hüfner-Dübel GmbH