

The "RKT" frame plug made of pure nylon with galvanised inner star screw enables fast and secure fastening in solid materials such as solid and natural stone, concrete and sand-lime brick. Its 4 side wings reliably prevent the plug from turning while the screw is being screwed in.

Temperature resistance: -40°F to +176°F

Safety coefficient: 5

Ø 8mm



Ø 10mm



Produktspezifikation

Article number	Dimension Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Installation depth min. mm	Effective length max. mm	Box contents	outer carton
11 210	8 x 60	8	50	45	20	100 pcs.	1.000 pcs.
11 210	8 x 80	8	50	45	40	100 pcs.	1.000 pcs.
11 210	8 x 100	8	50	45	60	100 pcs.	1.000 pcs.
11 210	8 x 120	8	50	45	80	100 pcs.	1.000 pcs.
11 210	8 x 140	8	50	45	100	50 pcs.	500 pcs.
11 210	8 x 160	8	50	45	120	50 pcs.	500 pcs.
11 210	10 x 80	10	60	50	30	50 pcs.	500 pcs.
11 210	10 x 100	10	60	50	50	50 pcs.	500 pcs.
11 210	10 x 120	10	60	50	70	50 pcs.	500 pcs.
11 210	10 x 140	10	60	50	90	50 pcs.	500 pcs.
11 210	10 x 160	10	60	50	110	50 pcs.	500 pcs.

Extraction values in kilo-Newton^{*}

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
10	4,5 kN	3,9 kN	3,9 kN

* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH