



Technical data sheet

scaffolding eye „EYE“

Ø 8mm

The eye bolt "EYE" Ø 8mm is made of galvanised steel and has a welded eye. Markings on the shaft indicate the correct setting depth when screwing in.

Temperature resistance:

Safety coefficient: 5



Product specification

Article number	Eye Inside Ø mm	Screws Ø mm	Screws shank length mm
20 000	15	8	50
20 000	15	8	80
20 000	15	8	100
20 000	15	8	120

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH

Important processing information

The eyelet must penetrate the respective dowel and be screwed in at least far enough to penetrate the dowel with its own diameter.

Additional parts suitable for the system



scaffolding plug „POWERDRIVE“

Art.: 10 400



scaffolding plug „POWERDRIVE WALL“

Art.: 10 450

Extraction values in kilo-Newton^{*}

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
14	19,8 kN	7,3 kN	6,1 kN

* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH

The eye bolt "EYE" Ø 12mm is made of galvanised steel and has a welded eye. Markings on the shaft indicate the correct setting depth when screwing in.

Temperature resistance:

Safety coefficient: 5



Product specification

Article number	Eye Inside Ø mm	Screws Ø mm	Screws shank length mm
20 000	23	12	90
20 000	23	12	120
20 000	23	12	160
20 000	23	12	190
20 000	23	12	230
20 000	23	12	300
20 000	23	12	350
20 000	23	12	400
20 000	23	12	450
20 000	23	12	500

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH

Important processing information

The eyelet must penetrate the respective dowel and be screwed in at least far enough to penetrate the dowel with its own diameter.

Additional parts suitable for the system




scaffolding plug „POWERDRIVE“

Art.: 10 400




scaffolding plug „POWERDRIVE WALL“

Art.: 10 450



Plug stopper „KREUZ“

Art.: 10 500



Plug stopper „RING“

Art.: 10 600

Extraction values in kilo-Newton^{*}

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
14	19,8 kN	7,3 kN	6,1 kN

* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH