

The metal cavity plug "MHDS" with pre-assembled screw is suitable for light to medium fixings on chipboard, plasterboard and gypsum fibreboard. Drill the hole as indicated, insert the plug flush and tighten the screw until resistance is felt. The points under the head prevent the plug from turning. Then loosen the screw and fix the component.

The "HRZ" professional cavity plug pliers are recommended for professional processing of ø 4mm, 5mm & 6mm.

Temperature resistance: -40°F to +392°F

Safety coefficient: 5



Product specification

Article number	Dimensions mm	Drill Ø mm	Screws Ø mm	Box Contents	Outer carton Contents
24 100	4 x 6	9	M 4	100 pcs.	2.000 pcs.
24 100	4 x 12	9	M 4	100 pcs.	1.000 pcs.
24 100	4 x 24	9	M 4	100 pcs.	1.000 pcs.
24 100	4 x 38	9	M 4	100 pcs.	1.000 pcs.
24 100	5 x 12	11	M 5	100 pcs.	1.000 pcs.
24 100	5 x 16	11	M 5	100 pcs.	1.000 pcs.
24 100	5 x 24	11	M 5	100 pcs.	1.000 pcs.
24 100	5 x 38	11	M 5	100 pcs.	1.000 pcs.
24 100	6 x 12	13	M 6	100 pcs.	1.000 pcs.
24 100	6 x 16	13	M 6	100 pcs.	1.000 pcs.
24 100	6 x 24	13	M 6	100 pcs.	1.000 pcs.
24 100	6 x 38	13	M 6	50 pcs.	500 pcs.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
#Hüfner-Dübel GmbH



Technical data sheet

Metal cavity plug "MHDS"

Extraction values in kilo-Newton^{*}

Plug Ø	Plasterboard 12,5 mm
4	0,86 kN
5	1,27 kN
6	1,53 kN

* All data is based on values determined during factory tests by Huefner-Dübel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
f #Hüfner-Dübel GmbH